



We specialize in manufacturing carbon steel tubes, serving different industries such as construction, greenhouse, furniture, metal mechanical, among others. Our facility is ISO 9001:2015 certified and we maintain an enduring commitment to continuous improvement and meeting our customers needs.

## Characteristics:

- High frequency welding.
- Galvanized and aluminized seam metallizing.
- Eddy Current online testing, as well as non-destructive testing to ensure welding quality.
- Destructive tests performed in order to guarantee mechanical property.

Tube	Size (In)	Thickness (In)	Lenght (In)
Round	0.625"-6.625"	0.359" - 0.2800"	119" - 500"*
Square	0.500" x 0.500" 5.000" x 5.000"	0.359" - 0.2500"	119" - 500"*
Rectangular	1.000" x 0.500" 8.000" x 3000"	0.359" - 0.2800"	119" - 500"*

\*Inquiry from 500" to 540" lenghts

## Mill Rolling Capacities

Round (in)		Rectangular (in)		Square (in)	
Description	Thickness	Description	Thickness	Description	Thickness
0.625"	0.0359-0.0747	1" x 0.5"	0.0478-0.0598	0.5" x 0.5"	0.0359-0.0478
0.75"	0.0359-0.0747	1.5" x 0.5"	0.0359-0.1196	0.625" x 0.625"	0.0359-0.0598
1"	0.0359-0.0747	1.25" x 0.75"	0.0359-0.1196	0.75" x 0.75"	0.0478-0.0747
1.050"	0.0359-0.1046	1.75" x 0.75"	0.0359-0.1196	1" x 1"	0.0359-0.1196
1.125"	0.0359-0.0747	1.5" x 1"	0.0359-0.1196	1.25" x 1.25"	0.0359-0.1196
1.250"	0.0359-0.1196	2" x 1"	0.0359-0.1196	1.5" x 1.5"	0.0359-0.1196
1.315"	0.0359-0.0747	2.25" x 0.75"	0.0359-0.1196	2" x 2"	0.0359-0.2500
1.375"	0.0359-0.0897	2.75" x 1"	0.0359-0.1196	2.5" x 2.5"	0.0478-0.2500
1.500"	0.0359-0.1196	2.5" x 1.25"	0.0359-0.1196	3" x 3"	0.0747-0.2500
1.625"	0.0359-0.0897	3" x 1"	0.0359-0.2500	3.5" x 3.5"	0.0747-0.2800
1.66"	0.0359-0.1196	2.5" x 1.5"	0.0359-0.2500	4" x 4"	0.0747-0.2800
1.75"	0.0359-0.0897	3" x 2"	0.0478-0.2500	4.5" x 4.5"	0.0747-0.2800
1.875"	0.0359-0.1196	4" x 2"	0.0747-0.2500	5" x 5"	0.1196-0.2800
2"	0.0359-0.0897	4" x 3"	0.0747-0.2800		
2.375"	0.0359-0.1196	5" x 2"	0.0747-0.2800		
2.5"	0.0359-0.2500	6" x 2"	0.0747-0.2800		
2.875"	0.0747-0.2500	5" x 3"	0.0747-0.2800		
3"	0.0478-0.1046	6" x 3"	0.1046-0.2800		
3.5"	0.0747-0.2800	6" x 4"	0.1196-0.2800		
4.5"	0.0747-0.2800	8" x 2"	0.1196-0.2800		
6.625"	0.1196-0.2800	8" x 3"	0.1196-0.2800		

  

Elliptical (In)	
Description	Thickness
0.767" x 1.210"	0.0359-0.0747

  

<b>ASTM A500</b>
<b>ASTM A513</b>
<b>ASTM A787</b>